



## Husqvarna LG 300

LG 300 is a compact, lightweight yet powerful reversible plate compactor is developed for smaller jobs, such as driveways and pathways, private house projects and narrow trenches. It is ideal when macadam beds are thinner and you need nimble, responsive handling. The Hatz 1B30 diesel engine with electric start reduces fuel consumption and emissions, quality components reduce vibrations. It is equipped with a durable Hardox 400-steel bottom plate.



### Easy operation

The forward/reverse lever and fixed handle grip make handling easy on all surfaces. You don't have to push/pull constantly during operation.



### Strong protection, easy transportation

The heavy-duty steel frame protects the engine and transmission. The frame is also equipped with a lifting eye for easy transportation.

### Plates made to last

The plates are made from the extremely durable and wear-resistant Hardox 400 steel. The special design keeps rocks from getting stuck between the plate and frame.



### Low handle vibration levels

Great engineering and quality components minimise handle vibration levels and strain, therefore contributing to a safer, more productive and enjoyable workday.



## FEATURES

- Plates made to last
- Strong protection, easy transportation
- Easy operation
- Low handle vibration levels

### Technical Specifications

#### ENGINE

|                              |                     |
|------------------------------|---------------------|
| Motor/engine model           | 4-stroke air-cooled |
| Power output                 | 4.7 kW              |
| Exhaust emissions (CO2 EU V) | 743 g/kWh           |
| Power/fuel type              | Diesel              |
| Fuel tank volume             | NaN gal (US)        |

#### SPECIFICATIONS

|                   |           |
|-------------------|-----------|
| Speed forward max | 0.03 km/h |
| Speed             | 25 m/min  |
| Starter           | Electric  |

#### DIMENSIONS

|                   |        |
|-------------------|--------|
| Plate length (mm) | 600 mm |
| Plate width       | 500 mm |
| Weight            | 302 kg |

#### SOUND AND NOISE

|                                       |           |
|---------------------------------------|-----------|
| Sound power level, guaranteed (LWA)   | 105 dB(A) |
| Sound pressure level at operators ear | 93 dB(A)  |

#### PACKAGING

|                  |                     |
|------------------|---------------------|
| Packaging length | 800 mm              |
| Packaging width  | 600 mm              |
| Packaging height | 1400 mm             |
| Packaging volume | 672 dm <sup>3</sup> |