



Husqvarna Vibrastar

Husqvarna Vibrastar is a reliable and robust series of concrete vibrators, designed for medium to high slump concrete. The ergonomic aluminum switchbox offers easy one-hand operation and reduces hand and arm vibrations. Dual fiber layers in the hose and oil lubricated bearings in the vibrator improve durability and reduce the need for regular maintenance.

Cost and energy efficient

Due to the low ampere consumption, the vibrator is energy-efficient as well as cost-effective.

Ergonomic design

The easy-to-use aluminum switchbox offers one-hand operation and reduced hand/arm vibrations, which means you can work longer without becoming fatigued.

Lots of up time

Robust and reliable, this vibrator is designed to handle medium to high slump concrete and deliver lots of uptime.

Service-friendly design

When it comes to maintenance, the service-friendly design makes replacing bearings fast and simple.

FEATURES

- Lots of up time
- Ergonomic design
- Cost and energy efficient
- Service-friendly design

Technical Specifications

ENGINE	
Output power	0.4 kW
SPECIFICATIONS	
Rated current	8 A
Phases	3 ph
Frequency	200 Hz
Voltage	42 V
Vibration value	3.28 m/s ²
DIMENSIONS	
Hose length	5 m
Cable length	10 m
Tube weight	3.06
PACKAGING	
Packaging length	800 mm
Packaging width	560 mm
Packaging height	160 mm
Packaging volume	72 dm ³

ACCESSORIES



HUSQVARNA CF 11 M
967 93 79-01



HUSQVARNA CF 25 T
967 91 34-02



HUSQVARNA CF 25 M
967 93 87-01



HUSQVARNA CF 67 T
967 93 82-01



HUSQVARNA CF 67 T CI4P
967 93 82-02



HUSQVARNA CF 67 T
967 93 82-03