



Husqvarna AX

Husqvarna AX is a series of concrete vibrators designed to handle all types of concrete. It is reliable, durable and powered for the toughest jobs. The ergonomic electric motor-in-head design provides outstanding performance. Maintenance-free and offering a 100% start-up rate, the AX vibrators fit most applications.

Tough, flexible materials

All cables and hoses offer excellent resistance, traction and bending properties.

Built to last

Equipped with roller bearings and induction hardened steel for extended service life. AX 36 and AX 40 have ball bearings.

Handles all types of concrete

Designed to help you handle all types of concrete – from high to low slump concrete and thin beams to extensive foundations.

Cover all concrete internal vibrations

Ideal when several diameters are required on the same work site as one frequency converter allows you to run up to four vibrators simultaneously.

FEATURES

- Handles all types of concrete
- Built to last
- Tough, flexible materials
- Cover all concrete internal vibrations

Technical Specifications

ENGINE	
Output power	0.8 kW
SPECIFICATIONS	
Rated current	11.7 A
Frequency	200 Hz
Frequency	12000
Voltage	42 V
Vibration value	3.66 m/s ²
DIMENSIONS	
Hose length	10 m
Tube diameter	56 mm
Cable length	10 m
Tube weight	5.1
PACKAGING	
Packaging length	840 mm
Packaging width	540 mm
Packaging height	210 mm
Packaging volume	95 dm ³

ACCESSORIES



HUSQVARNA CF 25 T
967 91 34-02



HUSQVARNA CF 25 M
967 93 87-01



HUSQVARNA CF 67 T
967 93 82-01



HUSQVARNA CF 67 T CI4P
967 93 82-02



HUSQVARNA CF 67 T
967 93 82-03



ELASTOMER END CAP
595 02 96-01