

Husqvarna AX

Husqvarna AX is a series of concrete vibrators designed to handle all types of concrete. It is reliable, durable and powered for the toughest jobs. The ergonomic electric motorin-head design provides outstanding performance. Maintenance-free and offering a 100% start-up rate, the AX vibrators fit most applications.

Tough, flexible materials

All cables and hoses offer excellent resistance, traction and bending properties.

Built to last

Equipped with roller bearings and induction hardened steel for extended service life. AX 36 and AX 40 have ball bearings.

Handles all types of concrete

Designed to help you handle all types of concrete – from high to low slump concrete and thin beams to extensive foundations.

Cover all concrete internal vibrations

Ideal when several diameters are required on the same work site as one frequency converter allows you to run up to four vibrators simultaneously.

FEATURES

- Handles all types of concrete
- Built to last

- Tough, flexible materials
- Cover all concrete internal vibrations

Technical Specifications	
ENGINE	
Output power	0.3 kW
SPECIFICATIONS	
Rated current	6.2 A
Frequency	200 Hz
Frequency	12000
Voltage	42 V
Vibration value	3.81 m/s ²
DIMENSIONS	
Hose length	5 m
Tube diameter	36 mm
Cable length	10 m
Tube weight	2.1
PACKAGING	
Packaging length	800 mm
Packaging width	570 mm
Packaging height	160 mm
Packaging volume	73 dm ³

ACCESSORIES



HUSQVARNA CF 11 M 967 93 79-01





HUSQVARNA CF 25 M 967 93 87-01



HUSQVARNA CF 67 T 967 93 82-01



HUSQVARNA CF 67 T CI4P 967 93 82-02



HUSQVARNA CF 25 T 967 91 34-02

HUSQVARNA CF 67 T 967 93 82-03