

# **Husqvarna SV Screed Section**

The truss screed sections for SV petrol/electric are ideal for large surfaces. High profile aluminum frames gives 30 % weight reduction compared to BT 90 screeds and ensures portability and productive usage in high to medium slump concrete. Designed for up to 25 m wide floors and handles depths of up to 150 mm. Can create a slab at the speed of one metre per minute. Applications are for example tunnels, roads and large depots. Easy to assemble by a single operator and adjust camber. Many configurations possible with accessories, such as winches and outriggers, to cover your day to day needs.



#### **Engineered to last**

Triangular frames, and square tubes provide better rigidity. Oscillating bearing with grease nipples extend the product life-time and serviceability.



## Easy setup

Easy to assemble by a single operator.



A precision turn-buckle allows to camber the screed sections independently.



#### Easy to transport

Modular system with strong, lightweight design.



#### **FEATURES**

- Smart design
- Easy setup

- Engineered to last
- Easy to transport

Technical Specifications	
SPECIFICATIONS	
Working width	300 cm
PACKAGING	
Packaging length	620 mm
Packaging width	3350 mm
Packaging height	500 mm

### **ACCESSORIES**



HUSQVARNA SVE 967 95 57-01



HUSQVARNA SVG 967 95 58-01



96



HUSQVARNA SV SCREED SECTIONHUSQVARNA SV SCREED SECTION 967 95 59-01 967 95 59-02





HUSQVARNA SV SCREED SECTIONHUSQVARNA SV SCREED SECTION 967 95 59-04