




Husqvarna SV Screed Section

The truss screed sections for SV petrol/electric are ideal for large surfaces. High profile aluminum frames gives 30 % weight reduction compared to BT 90 screeds and ensures portability and productive usage in high to medium slump concrete. Designed for up to 25 m wide floors and handles depths of up to 150 mm. Can create a slab at the speed of one metre per minute. Applications are for example tunnels, roads and large depots. Easy to assemble by a single operator and adjust camber. Many configurations possible with accessories, such as winches and outriggers, to cover your day to day needs.



Engineered to last

Triangular frames, and square tubes provide better rigidity. Oscillating bearing with grease nipples extend the product life-time and serviceability.



Easy setup

Easy to assemble by a single operator.

Smart design

A precision turn-buckle allows to camber the screed sections independently.



Easy to transport

Modular system with strong, lightweight design.



FEATURES

- Smart design
- Easy setup
- Engineered to last
- Easy to transport

Technical Specifications

SPECIFICATIONS

Working width 300 cm

PACKAGING

Packaging length 620 mm

Packaging width 3350 mm

Packaging height 500 mm

ACCESSORIES



HUSQVARNA SVE
967 95 57-01



HUSQVARNA SVG
967 95 58-01



HUSQVARNA SV SCREED SECTION
967 95 59-01



HUSQVARNA SV SCREED SECTION
967 95 59-02



HUSQVARNA SV SCREED SECTION
967 95 59-03



HUSQVARNA SV SCREED SECTION
967 95 59-04