



## Husqvarna DM 430

DM 430 is a powerful and sturdy electric core drill for medium to heavy core drilling where reliability and high productivity is needed, especially with large diameter core bits. Recommended diameter 100-450 mm. With aluminium motor housing to withstand tough handling and a carrying handle for ergonomic usage and additional impact protection of the drill motor. Equipped with Embedded Connectivity, an enhanced version of Husqvarna Fleet Services™ for data analytics and insights into the health of the machine. Suitable for water evacuation, ventilation, angle drilling, stitch drilling and when you need cut close to corners.



### Optimised RPM's

Enables high drilling performance.



### Ergonomic

Equipped with a carrying handle for easy transport and handling.

### Sturdy and durable

Equipped with an aluminium housing and the protective carrying handle ensures rough handling.



### Embedded Connectivity

An enhanced version of Husqvarna Fleet Services™. Enables data analytics and insights into the health of the machine.



## FEATURES

- Sturdy and durable
- Ergonomic
- Optimised RPM's
- Embedded Connectivity
- Quick connection
- Quick-release washer
- Functional design
- The LED indicator shows the load of the machine, allowing the operator to always drill at maximum pressure, for best performance.
- The machine uses pulsation to warn you of an approaching overload. This increases productivity and extends product life.
- Reliable gearbox
- To facilitate making a starter hole, speed is reduced by half using the Smart Start® button.
- Drilling holes in stepless adjustable angles.
- Drilling for installation of stair rails, fences, etc.
- Drilling horizontally.
- Drilling multiple holes next to each other to make openings.
- Drilling upwards and downwards.
- Drilling for water evacuation.

### Technical Specifications

<b>MOTOR</b>	
Electronic product	Yes
Frequency	50-60 Hz
Voltage	100-120 V
Rated input power	3.2 kW
<b>DRILLING EQUIPMENT</b>	
Drill bit diameter with stand, max	450 mm
Recommended drill bit diameter, min	100 mm
<b>SPECIFICATIONS</b>	
Water pressure, max	3 bar
Spindle thread, outer	1 1 / 4" 7 UNC
<b>TRANSMISSION</b>	
Number of gearbox speeds	3
<b>DIMENSIONS</b>	
Water connector	G 1 / 4"
Weight	15.5 kg
Product size length	586 mm
Product size width	138 mm
<b>SOUND AND NOISE</b>	
Sound power level, guaranteed (LWA)	112 dB(A)
Sound power level, measured	110 dB(A)
Sound pressure level at operators ear	92 dB(A)
<b>PACKAGING</b>	
Packaging length	665 mm
Packaging width	255 mm
Packaging height	300 mm

## ACCESSORIES



DRILL SNAP  
531 07 46-74



HUSQVARNA DS 500  
967 96 86-01



HUSQVARNA W 70 P  
967 66 47-06



SLURRY RINGS WSR  
593 56 30-01



SLURRY RINGS WSR  
593 56 30-02



SLURRY RINGS WSR  
593 56 30-03



SLURRY RINGS WSR  
593 56 30-04



SLURRY RINGS WSR  
593 56 30-05



SLURRY RINGS WSR  
593 56 30-06



HUSQVARNA DS 50 GYRO  
965 15 78-20



SLURRY COLLECTOR V-SHAPED  
531 07 46-22



SLURRY COLLECTOR V-SHAPED  
531 28 00-07



HUSQVARNA WT 15I  
599 58 23-02



HUSQVARNA WT 15I  
599 58 24-07



SLURRY COLLECTOR  
531 28 03-29