



Husqvarna PG 820

With 820 mm wide grinding width PG 820 is our most productive concrete floor grinder suitable for industrial applications. With planetary drive system and Dual Drive Technology™, PG 820 is one of the market's most powerful and efficient machines. Excellent choice for concrete floor preparation and repair as well as all polishing and grinding applications – both wet and dry. Perfect for HiPERFLOOR® concrete floor polishing system.

Motor	
Rated input power	12.5 kW
Rated current	27 A
Voltage	380-480 V
Phases	3 ph
Pins	5-pin
Frequency	50 Hz
Dimensions	
Product size length	1375 mm
Product size width	830 mm
Product size height	1235 mm
Weight	455 kg

820 mm
270 mm
250 rpm
1100 rpm
290 kg
Independent FWD/REV direction control on both grinding discs and planetary head.
3

Husqvarna PG 820 965 19 56-07

Features for PG 820

Best in class



Outstanding productivity and reliability.

High production rate



High power machinery with Dual Drive Technology™ capable of delivering high production rates, increasing profit and saving valuable time.

Dual Drive Technology™



Dual Drive Technology™ – fully independent control of both planetary and satellite grinding heads in regards to speed and direction of rotation.

Gear-driven planetary head



Gear-driven planetary head; premium quality belt for powering grinding heads.

Recommended tools for PG 820











G1410	3	P	CS
-------	---	---	----

G1420 3PCS

G1440 3PCS

G1480 3PCS

	G1410 3 PCS	G1420 3PCS	G1440 3PCS	G14/0 3PCS	G1480 3PCS
Concrete hard	• • •	•••	\bullet \circ \circ		
Concrete medium		• 0 0	• • 0	• 0 0	
Concrete soft				• • •	• • 0
Paint and thin epoxy	• 0 0	• • 0	• • •	• 0 0	• 0 0
Plastic-like ceramic glues		• 0 0	• • •		
Porous ceramic glues				• • •	• • 0
Rain-damaged concrete				• • 0	• • •
Semi-polished concrete	• • •	• 0 0			
Thick epoxy	• 0 0	• 0 0	• • •	• 0 0	
Vinyl glues	• 0 0	• • 0	• • •	• 0 0	• 0 0











	HiperFlex FP40	HiperFlex FP80	HiperFlex FT80	SharX' [™]	BHT 270
Concrete	• • •		• • •		
Concrete hard	• • •			• • •	• • •
Concrete medium	• • 0		• • 0		• • •
Concrete soft			• • •		• • •
Marble		• • •			
Paint and thin epoxy	• • 0				• • •
Plastic-like ceramic glues	• • 0				• • •
Porous ceramic glues					• • •
Rain-damaged concrete					• • •
Semi-polished concrete				• • •	• • •
Terrazzo		• • •	• • •		
Thick epoxy					• • •
Vinyl glues	• • •				• • •



CP 1200 series P1200 series for PG machines

Concrete hard	ullet $ullet$ $ullet$	$\bullet \bullet \bigcirc$
Concrete medium	• • •	• • •
Concrete soft	$\bullet \bullet \bigcirc$	• • 0
Terrazzo		• 0 0