



Husqvarna WSC 40

WSC 40 is a truly unique, wall saw chain attachment that converts your Husqvarna WS 482 HF and WS 440 HF from blade to chain sawing. Enables efficient and precise sawing of corners and small openings without overcutting. Installs easily on the spindle, and fits into the kerf without re-positioning the rail.

Motor

Output shaft RPM, max	3500 rpm
Max spindle torque	30 Nm
Spindle starting torque, Nm	25 Nm

Dimensions

Product size length	1000 mm
Product size width	160 mm
Product size height	380 mm
Weight	27 kg
Weight saw unit	17.5 kg

Cutting equipment

Cutting depth, max	400 mm
--------------------	--------

Transmission

Number of gearbox speeds	1
--------------------------	---

Sound and noise

Sound power level, guaranteed (LWA)	106 dB(A)
Sound power level, measured	105 dB(A)
Sound pressure level at operators ear	83 dB(A)

Other

Water flow, min	3.5 l/min
Water pressure, max	7 bar
Water temp at min flow, max	60 °C

Features for WSC 40

High precision



Enables you to cut neatly in and around corners. Reaches into really tight spots and small openings, without having to change to a handheld cutter.

No overcutting



For example, when cutting door openings.

Flush cutting



Handles cuts close to the floor, ceiling or wall.

Easy handling and ergonomic operation with compact design

Quick set up, simple to replace blade flange on the wall saw with WSC 40.

Recommended tools for WSC 40



PRO 20 WSC 40



PRO 45

Brick	● ○ ○	● ● ○
Concrete hard	● ● ●	● ○ ○
Concrete medium	● ● ○	● ● ●
Concrete soft	● ○ ○	● ● ○
Cured concrete hard		● ● ○
Cured concrete medium		● ● ●
Cured concrete soft		● ● ●
Highly reinforced concrete	● ● ●	● ● ○
Reinforced concrete	● ● ○	● ● ●