

# Husqvarna PG 510

The PG 510 is a planetary floor grinder with three grinding discs and a total grinding width of 515 mm. It is suitable for removing coatings, grinding and polishing concrete, etc. The grinding head on the PG 510 is effectively sealed to keep dust and moisture out. This greatly extends the lifetime of the bearings and belts. The PG 510 is ideal as a rental machine and suitable for both professional and semi-professional work. Quick-release couplings allow the grinding head to be separated from the chassis which can then be easily folded for transport. The grinder also has a digital hour meter.



## Easy to transport and set-up

The machine is light and fits easily in any car thanks to the compact design and foldable frame and dividable parts.



#### **Efficient dust management**

Self-adjusting floating cover with brush list follows the surface and gives a tight seal to prevent the dust from entering the working environment.



The speed is fixed and no settings are required. The machine also has an user-friendly logical control panel with overload protection.



## Planetary operation

The machine has three grinding discs making it suitable for a wide range of applications.



#### **FEATURES**

- The speed is fixed and no settings are required. The machine also has an user-friendly logical control panel with overload protection.
- Self-adjusting floating cover with brush list follows the surface and gives a tight seal to prevent the dust from entering the working environment.
- The machine is light and fits easily in any car thanks to the compact design and foldable frame and dividable parts.
- The machine has three grinding discs making it suitable for a wide range of applications.
- The grinding head is effectively sealed to keep dust and moisture out. This greatly extends the lifetime of the bearings and belts.
- Redi Lock® is an instant and hassle-free system for changing diamond tooling.
- Possibility to log operating hours.
- Redi Lock® is an instant and hassle-free system for changing diamond tooling. Robust system design ensures maximum protection and life of your diamond tools.

Technical Specifications	
MOTOR	
Rated current	9 A
Voltage	380-420 V
Phases	3
Pins	5
Frequency	50 Hz
OTHER	
Grinding width	515 mm
Grinding disc diameter	230 mm
Grinding disc speed max	558 rpm
Grinding pressure, max	79 kg
Direction of rotation	One Direction
Number of grinding discs	3
DIMENSIONS	
Product size length	1525 mm
Product size width	555 mm
Product size height	950 mm
Weight	133 kg
PACKAGING	
Packaging length	1000 mm
Packaging width	590 mm
Packaging height	1035 mm