




Genset image for illustration purposes only

Technical data		
Voltage	(V)	400
Frequency	(Hz)	50
Fuel		Gasoline
Performance class		G1
Acoustic pressure LpA a 7 m	(dB(A) @7m)	68
Acoustic power LwA	(dB(A))	96

Mechanical structure		
Length (L)	(mm)	960
Width (W)	(mm)	641
Height (H)	(mm)	667
Weight	(kg)	185
Fuel tank capacity	(l)	24
Wheels and handles		Optional

Dimensions



Note: These draw

Power ratings			
Prime	Prime	Standby	Standby
kW	kVA	kW	kVA
9.5	11.8	11.1	13.9
Power factor			0.8

Fuel consumption table

Load level	PRIME	Aut. (h)
	(L/h)	
75%	4.23	5.67
100%	5.64	4.26

Engine

General		
Engine Brand		Honda
Engine Model		GX630
R.P.M.		3000
Net Power	(kWm)	12.00
Fuel		Gasoline
No. of cylinders		2
Displacement	(cm ³)	688
Regulation type		Mechanical
Emission level		Stage V

Lubrication System		
Oil capacity	(l)	1.9
Engine Oil Guard		YES

Cooling System		
Cooling type		Air

Starting system	
Recoil	NO
Electric 12V	YES

Alternator

Alternator brand		Mecc alte
Alternator model		ET20FS-160/A
IP alternator		IP23
Peak power 163°/27°	(kVA)	12,50
Poles		2
Excitation system		AVR
		Brushes
Efficiency at 100% 125°/40°	(%)	76.5

Main features and options

Mains features

- Electrical key start (E)
- Large fuel tank
- Engine Oil Guard
- Automatic Voltage Regulation (A)
- Magneto-thermal protection
- Instrumentation, voltmeter, hourmeter
- Differential circuit breaker (D)
- Connector for remote start (C)
- Sockets
- CE noise compliance

Sockets configuration

SCHUKO 230V 16A IP54	1
2P+T CEE 230V 16A IP44	2
3P+N+T CEE 400V 16A IP44	1

Options

- Wheel kit
- ATB (Automatique Transfer Box) with AMF (Automatique start on Mains Failure) including connector
- Remote Start and Stop Wireless with connector

Regulations:

The generator set has a CE Marking that includes the following directives:

- 2006/42/CE Machine Safety.
- 2014/35/CE Low Voltage.
- 2014/30/CE Electromagnetic compatibility.
- 2005/88/CE Noise emission in the environment by equipment for use outdoors.
- 2016/1628/CE Gases and contaminating particles emissions.

Definitions

Prime Rating

PRIME POWER: Electrical power data available at a variable load without limits of hours per year. An overload of 10 % is allowed for 1 hour of every 12. In accordance with ISO 8528/1 (2005) – PRP

Standby

STANDBY POWER: Electrical power data at variable load in an emergency in accordance with standard ISO 8528/1 (2005) – ESP. Overloads of emergency power are not allowed.

Grupos Electr genos Europa, S.A. is a certified company with ISO 9001, ISO 14001, OHSAS 18001 and PECAL

Atlas Copco reserves the right to modify any characteristic of their equipment without prior warning.

All products are designed and engineered in Zaragoza Competence Center

Weight and dimensions of a standard generator set.

Non-contractual document

Grupos Electr genos Europa, S.A.

Central Offices:

Poligono pitarco II - Parcela 20

50450 Muel (Zaragoza) Espa a

Tel.: +34 976 145 432

Fax.: +34 976 145 431

DISTRIBUTED BY:



Please, contact your local Atlas Copco Dealer for more information