

# Husqvarna BMG 555SC

BMG 555SC is a triple disc grinder designed for various sizes of horizontal surface preparation applications. BMG 555SC is equipped as standard with a speed control system and has been designed for the mid-size grinder market. BMG 555SC is equipped with a smart easy-to-use keypad that gives you all relevant information such as Amps, Volt, rpm etc. In addition, the adjustable steering handle includes protection for the operating buttons. This is an ideal machine for companies dealing with removal of coating, concrete grinding or polishing applications.

#### Efficient dust management

This grinder is equipped as standard with a local dust exhaust of 76 mm diameter, a floating shroud and an extra nozzle for minimised dust exposure on the job site.

#### Plug and grind

This triple disc grinder is equipped as standard with a speed control system. It makes the machine ideal for all type of applications.

### Adjustable steering handle

The adjustable steering handle includes a smart easy-to-use keypad with all relevant information (Amps, Volt, rpm, etc).

## Time saving tool change

This floor grinder is standard delivered with the 185 mm diameter Slidemag adapter plates. These allow the Slidemag wings to be easily slid in and out.

## FEATURES

- Adjustable steering handle
- Plug and grind

- Efficient dust management
- Time saving tool change

| Technical Specifications |          |
|--------------------------|----------|
| MOTOR                    |          |
| Rated current            | 32 A     |
| Voltage                  | 400 V    |
| Phases                   | 3 ph     |
| Frequency                | 50-60 Hz |
| OTHER                    |          |
| Grinding width           | 555 mm   |
| Grinding disc diameter   | 185 mm   |
| Grinding disc speed min  | 50 rpm   |
| Grinding disc speed max  | 1100 rpm |
| Number of grinding discs | 3        |
| DIMENSIONS               |          |
| Product size length      | 2080 mm  |
| Product size width       | 595 mm   |
| Product size height      | 1172 mm  |
| Weight                   | 298 kg   |
| PACKAGING                |          |
| Packaging length         | 1200 mm  |
| Packaging width          | 800 mm   |
| Packaging height         | 1155 mm  |

# ACCESSORIES



WATER TANK 533 40 61-01



FRICTION TESTER BOT 3000E 53118 50-01



GLOSS METER MG6-SS 593 31 32-01



HARDNESS TEST MOH'S TEST KIT 593 31 69-01



GLOSS & DOI METER RHOPOINT IQ 593 31 15-01



ROUGHNESS TESTER MARSURF PS10 593 31 74-01



ICRI PROFILE PLASTIC CHIPSET 546 21 69-02



PENETRATION TEST KARSTEN PIPE TEST KIT 598 85 80-02



ICRI PROFILE CONCRETE SET 546 21 69-01