

Husqvarna HTC T6

HTC T6 is the second largest model of the grinders with Duratiq Technology, which stands for operational reliability, precision, control and power. It is a planetary grinder with three grinding discs. The machine features an intuitive digital control panel which gives you continuous feedback and thus control over the grinding process. The completely dustproof, hermetically sealed design of the grinding head and the electrical cabinet protects vital components and extends their lifetime. The well-balanced chassis design makes the HTC T6 floor grinder easy to operate, with superior ergonomics and advanced safety features.

FEATURES

Technical Specifications	
MOTOR	
Output power (As rated by the engine/motor manufacturer)	7.5 kW
Rated input power	7.5 kW
Rated current	15 A
Voltage	380-415 V
Phases	3 ph
Pins	3P+N+E
Frequency	50-60 Hz
OTHER	
Grinding width	600 mm
Grinding disc diameter	230 mm
Direction of rotation	Both directions
Number of grinding discs	3
DIMENSIONS	
Product size length	1385 mm
Product size width	657 mm
Product size height	1054 mm
Weight	384 kg
PACKAGING	
Packaging length	1400 mm
Packaging width	900 mm
Packaging height	1470 mm
Packaging volume	1776.6 dm³

ACCESSORIES



HUSQVARNA TOOL HOLDER ELASTIC/FLEXIBLE 593 31 92-02



FRICTION TESTER BOT 3000E 531 18 50-01

HUSQVARNA PAD HOLDER 593 31 47-03



GLOSS METER MG6-SS 593 31 32-01



HUSQVARNA TOOL HOLDER AIRFLOW 593 31 93-02



HARDNESS TEST MOH'S TEST KIT GLOSS & DOI METER RHOPOINT 593 31 69-01



HUSQVARNA RESIN HOLDER 593 31 48-02



593 31 15-01



ROUGHNESS TESTER MARSURF PS10 593 31 74-01



ICRI PROFILE PLASTIC CHIPSET 546 21 69-02



PENETRATION TEST KARSTEN PIPE TEST KIT 598 85 80-02



ICRI PROFILE CONCRETE SET 546 21 69-01