




Husqvarna HTC X6

HTC X6 is the second largest model of the grinders with DuratIQ Technology, which stands for operational reliability, precision, control and power. It is a planetary grinder with four grinding discs. The machine features an intuitive digital control panel which gives you continuous feedback and thus control over the grinding process. The completely dustproof, hermetically sealed design of the grinding head and the electrical cabinet protects vital components and extends their lifetime. The well-balanced chassis design makes the HTC X6 floor grinder easy to operate, with superior ergonomics and advanced safety features.



FEATURES

Technical Specifications	
MOTOR	
Output power (As rated by the engine/motor manufacturer)	7.5 kW
Rated input power	7.5 kW
Rated current	15 A
Voltage	380–415 V
Phases	3 ph
Pins	3P+N+E
Frequency	50–60 Hz
OTHER	
Grinding width	600 mm
Grinding disc diameter	230 mm
Direction of rotation	Both directions
Number of grinding discs	4
DIMENSIONS	
Product size length	1385 mm
Product size width	657 mm
Product size height	1054 mm
Weight	399 kg
PACKAGING	
Packaging length	1400 mm
Packaging width	900 mm
Packaging height	1470 mm
Packaging volume	1776.6 dm ³

ACCESSORIES



HUSQVARNA TOOL HOLDER
ELASTIC/FLEXIBLE
593 31 92-02



HUSQVARNA PAD HOLDER
593 31 47-03



HUSQVARNA RESIN HOLDER
593 31 48-02



HUSQVARNA TOOL HOLDER
AIRFLOW
593 31 93-02



FRICITION TESTER BOT 3000E
531 18 50-01




GLOSS METER MG6-SS
593 31 32-01




HARDNESS TEST MOH'S TEST KIT
593 31 69-01



GLOSS & DOI METER RHOPOINT
IQ
593 31 15-01



ROUGHNESS TESTER MARSURF
PS10
593 3174-01



ICRI PROFILE PLASTIC CHIPSET
546 2169-02



PENETRATION TEST KARSTEN
PIPE TEST KIT
598 8580-02



ICRI PROFILE CONCRETE SET
546 2169-01