




Husqvarna PG 280 S

The PG 280 S is a basic, entry-level floor grinding machine. It effectively removes adhesives, paints, epoxy coatings and levelling compounds. It has a grinding width of 280 mm making it suitable for small to medium-sized concrete floors. Quick-release couplings allow the grinding head to be easily disconnected from the chassis when transporting the machine. Only available as a single-phase machine.



Separable parts

Quick-release couplings allow the chassis and motor to be easily disconnected.



Efficient dust management

Self-adjusting floating cover with brush list follows the surface and gives a tight seal to prevent the dust from entering the working environment.

Easy to use

The speed is fixed and no settings are required. The machine also has an user-friendly logical control panel with overload protection.



Time saving tool change

Redi Lock® is an instant and hassle-free system for changing diamond tooling.



FEATURES

- The speed is fixed and no settings are required. The machine also has an user-friendly logical control panel with overload protection.
- Self-adjusting floating cover with brush list follows the surface and gives a tight seal to prevent the dust from entering the working environment.
- Quick-release couplings allow the chassis and motor to be easily disconnected.
- Redi Lock® is an instant and hassle-free system for changing diamond tooling.

Technical Specifications

MOTOR	
Output power (As rated by the engine/motor manufacturer)	1.54 kW
Rated current	13 A
Voltage	220–240 V
Phases	1 ph
Pins	2
Frequency	50 Hz
OTHER	
Grinding width	280 mm
Grinding disc diameter	280 mm
Grinding disc speed max	1410 rpm
Grinding pressure, max	25 kg
Number of grinding discs	1
DIMENSIONS	
Product size length	1185 mm
Product size width	430 mm
Product size height	980 mm
Weight	76 kg
PACKAGING	
Packaging length	870 mm
Packaging width	470 mm
Packaging height	905 mm
Packaging volume	370.1 dm ³