



Husqvarna VARI-DRILL D810

Speedy and versatile for a wide range of applications. Exclusive segment shape for less friction. Exclusive crown shape on diameters below 50. Shorter length and thin walled tube for handheld machines.

Laser welded

Segments are attached to the tube by laser welding to minimise the risk of segment loss.

Wide application window

Designed to cover a wide window of applications for problem-free drilling with most drill motors and materials.

Smooth and rapid drilling

Thin tube and segments with lighter weight enables smooth and rapid drilling especially for handheld applications.

Several smart accessories available

With accessories such as adapters, centering devices and extenders the drill job can be made easier.

FEATURES

- Thin tube and segments with lighter weight enables smooth and rapid drilling especially for handheld applications.
- Designed to cover a wide window of applications for problem-free drilling with most drill motors and materials.
- Segments are attached to the tube by laser welding to minimise the risk of segment loss.
- With accessories such as adapters, centering devices and extenders the drill job can be made easier.
- Great versatility for handheld wet cutting.

Technical Specifications

GENERAL

Article Description	56 2.7X5X350 1/2" D810TW
Performance grade	Silver
Number of segments	5
Assembly	Brazed
Drill connection	1/2"
Coolant	Wet / dry
Power range, min kW	1.5 kW
Power range, max kW	2.5 kW
Power range, min hp	2.01 hp
Power range, max hp	3.35 hp

DIMENSIONS

Diameter mm	56 mm
Core length mm	350 mm
Segment height mm	7 mm
Segment length mm	24 mm
Segment width mm	2.7 mm
Article gross weight	927 g
Article net weight	800 g

MATERIALS

Asphalt	Acceptable
Block	Good
Brick	Good
Concrete hard	Optimal
Concrete medium	Optimal
Concrete soft	Optimal
Abrasive cured concrete	Good
Natural stone	Optimal
Natural stone sandstone	Optimal

PACKAGING

Packaging length	105 mm
Packaging width	105 mm
Packaging height	508 mm