



Husqvarna ELITE-DRILL D1405

Flexible diameters

In addition to the standard diameters, other diameters are available upon request.

Flexible core length

The standard core lengths are 450 mm and 500 mm (CR128), but other tube lengths are available on request.

Ideal for concrete and hard materials

Developed for fast cutting in universal construction materials, with a focus on hard materials like granite and hard concrete.

Possible to customise

This extensive series covers most applications, and customised tools can be arranged upon request.

FEATURES

- Developed for fast cutting in universal construction materials, with a focus on hard materials like granite and hard concrete.
- The standard core lengths are 450 mm and 500 mm (CR128), but other tube lengths are available on request.
- In addition to the standard diameters, other diameters are available upon request.
- This extensive series covers most applications, and customised tools can be arranged upon request.
- The segments are firmly fixed on the steel tube, notched into the tube and a high-resistance solder is used.
- Low active surface and evenly distributed cutting edges reduce the friction, which results in a faster drilling.
- With accessories such as adapters, centering devices and extenders the drill job can be made easier.
- Easy drilling with high speed.

Technical Specifications	
GENERAL	
Article Description	52 35x5x500 CR128 D1405
Performance grade	Gold
Number of segments	5
Assembly	Brazed
Drill connection	CR128
Coolant	Wet
Power range, min kW	2.4 kW
Power range, max kW	9 kW
Power range, min hp	3.2 hp
Power range, max hp	12 hp
DIMENSIONS	
Diameter mm	52 mm
Core length mm	500 mm
Segment height mm	9 mm
Segment length mm	24 mm
Segment width mm	35 mm
Article gross weight	1527 g
Article net weight	1400 g
MATERIALS	
Concrete hard	Optimal
Concrete medium	Good
Concrete soft	Acceptable
Granite	Optimal
Highly reinforced concrete	Optimal
Natural stone	Optimal
Reinforced concrete	Optimal
PACKAGING	
Packaging length	58 mm
Packaging width	58 mm
Packaging height	580 mm