

Husqvarna ELITE-DRILL D1510 Z-EDGE

Smooth and rapid drilling

Thin tube and segments with lighter weight enables smooth and rapid drilling especially for handheld applications.

High speed and free cutting

High speed and free cutting.

Optimised diamond selection

Optimal diamond selection enables the highest performance available for a wide range of conditions and applications.

FEATURES

- Optimal diamond selection enables the highest performance available for a wide range of conditions and applications.
- High speed and free cutting.

• Thin tube and segments with lighter weight enables smooth and rapid drilling especially for handheld applications.

| Technical Specifications | |
|--------------------------|----------------------------|
| GENERAL | |
| Article Description | 92 4.0x9x500 CR128 D1510-Z |
| Performance grade | Gold |
| Number of segments | 9 |
| Assembly | Laser welded |
| Drill connection | CR128 |
| Coolant | Wet |
| Power range, min kW | 2.4 kW |
| Power range, max kW | 9 kW |
| Power range, min hp | 3.2 hp |
| Power range, max hp | 12 hp |
| DIMENSIONS | |
| Diameter mm | 92 mm |
| Core length mm | 500 mm |
| Segment height mm | 9 mm |
| Segment length mm | 24 mm |
| Segment width mm | 4 mm |
| Article gross weight | 3445 g |
| Article net weight | 3200 g |
| MATERIALS | |
| Concrete medium | Good |
| Natural stone | Good |
| Reinforced concrete | Optimal |
| PACKAGING | |
| Packaging length | 104 mm |
| Packaging width | 105 mm |
| Packaging height | 580 mm |