



Husqvarna ELITE-DRILL D10 TW

Part of our Gold series, Elite-Drill D10 TW is the primary choice for the DM 540i drill motor, designed to cut at high speed without requiring too much load while providing optimal utilisation of the DM 540i's battery power. Suitable for handheld wet operation on lightly reinforced concrete and occasionally building bricks. Connector ½", available in diameters 10-100 mm.



Increased power and performance

Together with the DM 540i and this drill bit you can get up to 20% longer coring length on one battery charge and 25% faster drilling speed.*
*) According to internal tests conducted vs closest competitor in similar battery core drilling application in reinforced concrete.



Self-centering for quick and precise start

The roof-top design of the segment helps to centre the drill when applied. This ensures fast, consistent drilling speed from when the drill bit is new until it reaches the end of its product life.

Smooth and fast drilling speed

Developed for smooth and fast cutting in various types of concrete, including lightly reinforced concrete. The thin-walled segments and the optimised diamond and bond specification facilitates handheld drilling operation, relieving you from having to press too hard while achieving the result faster.



Wide range

Available in a wide range of diameters and lengths.



FEATURES

- Smooth and fast drilling speed
 - Self-centering for quick and precise start
- Increased power and performance
 - Wide range

Technical Specifications	
GENERAL	
Article Description	10 2,3x1x200 1/2" D10TW
Performance grade	Gold
Number of segments	1
Assembly	Laser welded
Drill connection	1/2"
Coolant	Wet
Power range, min kW	1.8 kW
Power range, max kW	3 kW
Power range, min hp	2.4 hp
Power range, max hp	4 hp
DIMENSIONS	
Diameter mm	10 mm
Core length mm	200 mm
Segment height mm	7.5 mm
Segment width mm	2.3 mm
Article gross weight	324 g
Article net weight	224 g
MATERIALS	
Block	Good
Brick	Good
Reinforced concrete	Optimal
PACKAGING	
Packaging length	55 mm
Packaging width	55 mm
Packaging height	580 mm