

Husqvarna K 1 PACE

K 1 PACE high power battery cutter has the power and performance you expect from equivalent petrol-powered cutters. Equipped with X-Halt™ brake function for operational safety. Ergonomic and user-friendly with low vibrations, optimally balanced machine and zero CO emissions during use. With built-in connectivity so you can easily monitor machine location, runtime, service intervals and receive wireless updates through FOTA (firmware over the air). Powered by Husqvarna PACE battery system with high power and fast charging for impressive productivity and a well-suited match with our specially designed battery blade range for maximised cutting depth and optimised performance. Suitable for concrete pipes, conrete garden plates, cinder blocks etc.

Zero CO emissions during use

Enjoy the freedom of working with an electric machine. Explore the potential of new applications by running the machine indoors or in urban areas where emissions or noise levels might be regulated.



Safe operation

X-Halt[™] blade brake function capable of stopping the rotation of the blade in fractions of a second.

Powerful

Power and performance in par with equivalent petrol-powered cutters. With an integrated gearbox for higher torque. For high productivity.



Red Dot award

This product is the recipient of a Red Dot award for high design quality.



FEATURES

- Powerful
- Safe operation
- Zero CO emissions during use
- Red Dot award
- Flexible
- Ergonomic and user-friendly
- High power PACE battery system
- A more sustainable choice

- Built-in connectivity
- Smart battery placement
- In-house developed brushless motor provides a high and consistent torque.
- Perfect balance
- Ergonomic handles
- Easy to change bladeguard position
- Anti-vibration system

Technical Specifications	
EQUIPMENT	
Cutting depth, max	145 mm
Blade diameter, max	361 mm
Arbor diameter	25.4/20 mm
Blade thickness, max	1.8 mm
Peripheral speed, max	59 m/s
DIMENSIONS	
Product size width	233 mm
Product size height	423 mm
SOUND AND NOISE	
Sound power level, measured	112.9 dB(A)
Sound pressure level at operators ear	101.9 dB(A)
VIBRATIONS	
Vibrations left/front handle	2.2 m/s ²
Vibrations right/rear handle	1.2 m/s²
PACKAGING	
Packaging length	823 mm
Packaging width	354 mm
Packaging height	759 mm
Packaging volume	86.8 dm ³

ACCESSORIES



HUSQVARNA WT 15I 599 58 23-01



HUSQVARNA WT 15I 599 58 23-02



HUSQVARNA WT 15I 599 58 23-04



HUSQVARNA WT 10MP 536 08 98-01



HUSQVARNA B380X PACE 970 49 41-01



HUSQVARNA B380X/C900X PACE POWER KIT 970 69 93-01



HUSQVARNA B750X PACE 970 49 42-01



HUSQVARNA B750X/C1800X PACE POWER KIT 970 69 95-01



HUSQVARNA C900X PACE 970 49 50-01



HUSQVARNA C1800X PACE 970 49 51-01



VAC ATTACHMENT 529 57 79-01



BATTERY TRANSPORTATION BOX 531 21 54-02



HUSQVARNA JACKET PE10J SMARTGUARD™ 536 50 50-01



HUSQVARNA JACKET PE10J SMARTGUARD™ 536 50 51-01



HUSQVARNA JACKET PE10J SMARTGUARD™ 536 50 52-01



HUSQVARNA JACKET PE10J SMARTGUARD™ 536 50 53-01



HUSQVARNA JACKET PE10J SMARTGUARD™ 536 50 54-01



HUSQVARNA WL 8I 970 58 49-01



HUSQVARNA HELMET PE10H SMARTGUARD™ 536 50 46-01



HUSQVARNA HELMET PE10H SMARTGUARD™ 536 50 47-01