



# TR 3.60 C5 PORTABLE POWER WATERPUMP Range AQUALINE INTENS

#### **PRODUCT ADVANTAGES**

- HONDA Professional Engine
- · Resistant pump-barrel
- Automatic priming
- · Easy acces to the turbine
- Offeres accessories

The AQUALINETM INTENS TR 2.36 H and TR 3.60 H models have a very high quality pump body and are designed for treating dirty water intensively and reliably. The front cover can be removed for quick cleaning, which is a considerable help for professionals.

STAGE V (2016/1628 EU): This product is compliant with regulation for implementing requirements relating to gaseous and pollutant emission limits in Europe

#### Range AQUALINE INTENS

Designed for water with low solid content.

















### TR 3.60 C5

#### WATER PUMP SPECIFICATIONS

Range	AQUALINE INTENS
Type liquid	Heavily sedimented water pump
Suction diameter [mm]	76
Backflow diameter (mm)	76
Outflow maximum (L/min)	900
Outlflow maximum (m3/h)	54
Lifting height (m)	26
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes
Fuel	Petrol
Tank (L)	3,10
75% cons. (I/h) *	0,90
75% Autonomy (h) *	3,40
Sound power level guaranteed LwA dB(A)	105
Acoustic pressure level @1m in dB(A)	91
Acoustic pressure level @7m in dB(A)	76

#### **ENGINE SPECIFICATIONS**

Engine brand	HONDA
Engine ref.	GX160_C5
Engine Type	O.H.V.
Start	Starter
Oil shutdown	Oui
Displacement (cm3)	163
Oil system capacity including filters (I)	0,60

#### **DIMENSIONS AND WEIGHT**

Length (cm)	50,50
Width (cm)	39,80
Height (cm)	46,60
Dry Weight (kg)	29

#### **PACKAGING**

Packaging type	Box
Length (cm)	51,50
Width (cm)	42
Height (cm)	48
Weight (kg)	34,50
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	157
weight of the packaged Pallet (kg)	424





## TR 3.60 C5

#### **ACCESSORIES SUPPLIED**



Inlet filter

**RBH0-5** 

**RHO** 

**R12** 

**R14** 

Circlips



Screw-on connectors

DOEST.

User and maintenance manual



**OPTIONS** 

RBH1 Box of 24 o.5L cans of oil or 20 1 L cans of oil (SAE 15W40)



Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).



Cover for SDMO 's generating sets, welding sets and water pumps



Piping kit for 3 water pumps made up of 5 m suction + 25 m lift.



Rapid connections kit for 3 water pumps.

